

# ACRYLIC LACQUER – PRODUCT DATA SHEET

## PRODUCT INFORMATION:

PRODUCT: Air dry Acrylic Lacquer  
Used for touch-up of Polyester coated  
Building Sheet Panels.

## PRODUCT DESCRIPTION:

Color – Standard and Metallic Colors  
Gloss – 25 – 85  
VOC – 720 g/l – 6.25 lbs/gal.  
Weight/Gal. – 9.25 lbs. +/- .015  
Flash Point – 78 OF. (25.6 0 C)  
Package – 2 Oz. bottles, pt. qt. gal  
Percent Solids by wgt. – 36% by wgt.  
Percent Solids by Vol. – 21% by vol.

## DRY SCHEDULE:

Air Dry @ 77 OF @ 50% relative humidity  
Dry to touch – 5 – 10 minutes  
Dry to handle – 15 - 30 minutes  
Dry to re-coat – 30 minutes minimum

## APPLICATION DATA:

Substrate: Damaged Polyester Panel.

Substrate Preparation: Surface must be free from  
Foreign contaminants. Scuff sand or clean the damaged  
Area with paint thinner such as Naptha or Mineral Spirits.

Apply one coat of touch-up to the damaged areas only. A  
Small artists brush is included in the 2 ounce bottle to apply  
The material. The touch-up is supplied ready to apply.

## CLEAN UP:

Clean up with lacquer thinner .