



ACRYLIC LACQUER – PRODUCT DATA SHEET

PRODUCT INFORMATION:

PRODUCT: Air dry Acrylic Lacquer
Used for touch-up of Polyester coated
Building Sheet Panels.

PRODUCT DESCRIPTION:

Color – Standard and Metallic Colors
Gloss – 25 – 85
VOC – 720 g/l – 6.25 lbs/gal.
Weight/Gal. – 9.25 lbs. +/- .015
Flash Point – 78 OF. (25.6 0 C)
Package – 2 Oz. bottles, pt. qt. gal
Percent Solids by wgt. – 36% by wgt.
Percent Solids by Vol. – 21% by vol.

DRY SCHEDULE:

Air Dry @ 77 OF @ 50% relative humidity
Dry to touch – 5 – 10 minutes
Dry to handle – 15 - 30 minutes
Dry to re-coat – 30 minutes minimum

APPLICATION DATA:

Substrate: Damaged Polyester Panel.

Substrate Preparation: Surface must be free from
Foreign contaminants. Scuff sand or clean the damaged
Area with paint thinner such as Naptha or Mineral Spirits.

Apply one coat of touch-up to the damaged areas only. A
Small artists brush is included in the 2 ounce bottle to apply
The material. The touch-up is supplied ready to apply.

CLEAN UP:

Clean up with lacquer thinner .